

KERALA CRICKET ASSOCIATION

**NAME OF WORK : CONSTRUCTION OF ROAD FROM MAIN ENTRANCE TO GROUND WITH SAUCER DRAINAGE ON BOTH SIDES OF ROAD AT S. D
COLLEGE CRICKET GROUND, ALAPPUZHA**

TENDER SCHEDULE

Item No	Quantity	Unit	Details of work	Rate in figures	Unit	Rate in words	Amount
1	100.00	m3	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains, including dressing of sides and ramming of bottoms, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m and lift upto 1.5m.		/m3		
2	705.00	m2	Preparation and consolidation of sub grade with power road roller of 8 to 12 tonne capacity after excavating earth to an average of 22.5 cm depth, dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surplus earth with lead upto 50 metres.		/m2		
3	13.00	m3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size) for base course		/m3		
4	139.00	m2	Centering and shuttering including strutting, propping etc. and removal of form for all heights : Foundations, footings, bases of columns, etc. for mass concrete		/m2		

5	6.50	m3	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:2:4 (1 cement : 2 coarse sand (zone-III) : 4 graded stone aggregate 20 mm nominal size)		/m3		
6	225.00	m3	Providing , laying spreading and compacting graded stone aggregate (size range 53 mm to 0.075 mm) to wet mix macadam (WMM) specification including premixing the material with water at OMC in mechanical mix plant, carriage of mixed material by tipper to site, for all leads & lifts, laying in uniform layers with mechanical paver finisher in sub - base / base course on well prepared surface and compacting with vibratory roller of 8 to 10 tonne capacity to achieve the desired density, complete as per specifications and directions of Engineer - in- Charge.		/m3		
7	825.00	m2	Supplying and laying interlocking tile 100 mm or nearest size thickness, minimum strength M 40 including providing a layer of 6 mm aggregate for 5 cm thickness, then laying interlock cobbles in lines and levels as per the directions of the Engineer in charge at site inclusive of all cost & conveyance charges etc.; complete.		/m2		
8	1.50	m3	Solid block masonry using pre cast solid blocks (Factory made) of size 30x20x15 cm or nearest available size confirming to IS 2185 part I of 1979 for foundation, plinth and wall with thickness 15cm in: CM 1:6 (1 cement :6 coarse sand) etc		/m3		
9	300.00	m2	15 mm cement plaster on rough side of single or half brick wall of mix: 1:4 (1 cement: 4 coarse sand)		/m2		

10	80.00	m2	Finishing walls with Acrylic Smooth exterior paint of required shade: New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm)		/m2		
			TOTAL				
						Add GST @ 18 %	
						TOTAL	

Rounded to Rs.

Rupees in words :

Signature of
Contractor:

Name and address

Place :

Date :