Page1/8

KERALA CRICKET ASSOCIATION

NAME OF WORK: PAINTING PAVILION , INDOOR AND ALLIED WORKS AT CRICKET GROUND, PERINTHALMANNA, MALAPPURAM.

TENDER SCHEDULE

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
			APPENDIX - A - PAVILION				
1	1700.00	sqm	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	/sqm			
2	1700.00	sqm	Finishing walls with Acrylic Smooth exterior paint of required shade : Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cementpaint surface				
3	25.00	sqm	Dismantling the existing damaged tiles at bath rooms, floors etc wherever required and disposing carefully to a distance of 200 m away from the source including all labour charges etc complete. as per the direction of Engineer in charge.	/sqm			
4	25.00	sqm	Providing and fixing 1st quality ceramic glazed floor tiles conforming to IS :15622 (thickness to be specified by the manufacturer) of approved make in allcolours, shades except burgundy, bottle green, black of any size as approvedby Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thickbed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cementslurry @ 3.3kg per sqm including pointing in white cement mixed with pigmentof matching shade etc complete as per the direction of Engineer in charge. (Base rate of tile at show room Rs.600/sqm)	/sqm			

Page2/8

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
5	10.00	Nos	Dismantling the existing damaged pvc doors and disposing carefully to a distance of 200 m away from the source including all labour charges etc complete as per the direction of Engineer in charge.	/each			
6	45.00	m	Providing and fixing Fiber Glass Reinforced plastic (FRP) Door Frames of crosssection 90 mm x 45 mm having single rebate of 32 mm x 15 mm to receive shutter of 30 mm thickness. The laminated shall be moulded with fire resistant grade unsaturated polyester resin and chopped mat. Door frame laminate shall be 2 mm thick and shall be filled with suitable wooden block in all the three legs. The frame shall be covered with fiber glass from all sides. M.S. stay shall be provided at the bottom to steady the frame etc complete as per the direction of Engineer in charge.	/m			
7	14.00	sqm	Providing and fixing to existing door frames 30 mm thick Glas Fibre Reinforced Plastic (FRP) panelled door shutter of required colour and approved brand and manufacture, made with fire - retardant grade unsaturated polyester resin, moulded to 3 mm thick FRP laminate for forming hollow rails and styles, with wooden frame and suitable blocks of seasoned wood inside at required places for fixing of fittings, cast monolithically with 5 mm thick FRP laminate for panels conforming to IS : 14856, including fixing to frames etc complete as per the direction of Engineer in charge.	/sqm			
8	9.00	Nos	Dismantling the existing damaged european water closets with all accessories and disposing it to a distance of 200 m including all labour charges etc complete.as per the direction of Engineer in charge.	/each			

Page3/8

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
9	9.00	Nos	Providing and fixing premiume quality floor mounting european water closet with seat cover having single moulding unit with flishing system of approved make (Cera/Parryware/Somany or equivalent) including cost of all fittings, fitting charge etc complete as per the direction of Engineer in charge.	/each			
10	1.00	no	Providing and fixing premiume quality urinal partition with all accessories, including cutting and making good the walls and floors wherever required. (Parryware/Cera/Somany or equivalent) including cost of all fittings, fitting charge etc complete as per the direction of Engineer in charge.				
11	6.00	nos	Providing and fixing premiume quality urinal partition with all accessories, including cutting and making good the walls and floors wherever required. (Parryware/Cera/Somany or equivalent) including cost of all fittings, fitting charge etc complete as per the direction of Engineer in charge.	/each			
12	8.00	nos	Providing and fixing premiume quality S.S shower head with shower arm 300 mm long or required size (Jaquar/ Grohe/Parryware etc.) including cost of all materials and labour charges etc.complete. as per the direction of Engineer in charge.	/each			
13	5.00	nos	Providing and fixing premiume quality brass CP pillar tap for wash basin (Jaquar/ Grohe/Parryware etc.) including cost of all materials and labour charges etc.complete. as per the direction of Engineer in charge.	/each			
14	5.00	nos	Providing and fixing premiume quality brass angle cock (Jaquar/ Grohe/Parryware etc.) including cost of all materials and labour charges etc.complete. as per the direction of Engineer in charge.	/each			

Page4/8

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
15	10.00	m2	Supplying and fixing in position 5 mm thick mirror of adequate size as per requirements ,fixing in SS stud etc including cost of all materials, labour charges for fixing etc. as per the direction of Engineer in charge.	/sqm			
16	17.00	nos	Supplying and fixing S S Floor Grattings of size 100 x 100 mm in good quality, including cost of all materials and labour charges etc, complete.	/each			
			APPENDIX - B : KITCHEN BLOCK				
17	200.00	m2	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	/sqm			
18	200.00	m2	Finishing walls with Acrylic Smooth exterior paint of required shade : Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cementpaint surface	/sqm			
19	110.00	m2	Providing and fixing 25 mm x 25 mm x 16 gauge thick GP square tubes for outer frames and verticals for fixing 4.00 mm thick GI weld mesh of size 25 x 40 mm for kitchen and store side walls and wherever necessary etc and applying one coat epoxy primer and two coat epoxy mat finish paint, Including cost and conveyance of all materials to site labour charges etc, complete as per the direction of Engineer in charge.	/sqm			
20	10.00	m2	Providing and fixing in position of MS doors openable with single shutter, masonry opening size of 150 cm span,opening height of 225 cm or as per requirement as site, with outer frame for 2 sides and top and shutters openable in one directions with shutter frame all around with all accessories (Lock, tower bolts, handle etc) including cost and conveyance of all material and labour charges etc, complete as per the direction of Engineer in charge.	/sqm			

Page5/8

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
			APPENDIX - C : INDOOR BUILDING				
21	80.00	m2	Providing and fixing 50 mm Expanded polyethylene foam seets (EPE foam sheets) for protecting the side walls of indoor buliding from ball hit including 25 mm or nearest size aluminiume beadding, 80 mm or nearest size drive wall screws etc completeincluding cost and conveyance of all material and labour charges etc, complete as per the direction of Engineer in charge.	/sqm			
22	100.00	m2	Providing and fixing cloth curtains having hard enough to prevent lights in wickets at front side of practice wickets including cost and conveyance of all materials to site, labour charges etc,complete as per the direction of Engineer in charge.	/sqm			
23	40.00	m2	Providing and fixing 25 mm x 25 mm x 16 gauge thick GP square tubes for outer frames and vertical members and fixing 0.35 mm thick powder coated traffold sheet for store side covering, applying one coat epoxy primer and two coat epoxy mat finish paints, Including cost and conveyance of all materials to site labour charges etc, complete as per the direction of Engineer in charge.	/sqm			
24	15.00	no	Reconditioning / setting the damaged aluminium door, including cost and conveyance of all damaged fittings, material and labour charges etc, complete as per the direction of Engineer in charge.	/each			
25	150.00	m2	Replace the damaged roof sheets with new ones of thicknes 0.40 mm thick or nearest available size powder coated galvanised traffold sheet for indoor roof and stacking the old and replaced sheets to a distance of 200 m Including cost and conveyance of all materials to site labour charges etc, complete. as per the direction of Engineer in charge.	/sqm			

Page6/8

Item No	Quantity	Unit	Details of work	Rate in	Unit	Rate in words	Amount
26	900.00	m2	Painting with synthetic enamel paint two coat with quality pints approved by the Engineer in charge after scrapping and sand papering, levelling to smooth even finish including cost and conveyance of all materials to site, labour charges, hire and labour charges of scaffolding etc,complete for structural steel sections as directed by the Engineer in charge	fugures /sqm			
27	1000.00	m2	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	/sqm			
28	1000.00	m2	Finishing walls with Acrylic Smooth exterior paint of required shade : Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cementpaint surface	/sqm			
29	20.00	m2	Providing and fixing 25 mm x 25 mm x 16 gauge thick GP square tubes for outer frames and fixing 2 mm thick poly carbon sheet for side covering indoor west side, applying one coat epoxy primer and two coat epoxy enamel mat finish paints, Including cost and conveyance of all materials to site labour charges etc, complete as per the direction of Engineer in charge.	/sqm			
30	40.00	m	Supplying & fixing 200 mm dia or nearest available size PVC Rain Water Gutter pipes, PVC Rain water system, to connect half round section fitted with deep rubber Gasket and clips must be screwed directly to fascia or anchored by a suitable rafter bracket.The details of fittings are pipe support bracket, stop end etc. Including cost and conveyance of all fittings and materials to site, labour charges etc. complete.	/sqm			
			APPENDIX - D : MISCELLANEOUS WORKS				

Page7/8

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
31	20.00	m3	RR with Departmental. Stone - Random rubble masonry using departmental rubble in foundation and plinth including through and bond stone and levelling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size) upto plinth level with Cement mortar 1:6 (1 cement : 6 coarse sand).	/cum			
32	20.00	m3	Dry rubble masonry with hard stone in foundation and plinth including levelling up with cement concrete 1:6:12 (1cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size) including cost of through stone and bond stone.	/cum			
33	25.00	m2	Centering and shuttering including strutting, etc. and removal of form for foundations, footings, bases of columns, belts etc Including cost and conveyance of all materials to site labour charges etc, complete as per the direction of Engineer in charge.	/sqm			
34	7.00	m3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:2:4 (cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	/cum			
35	500.00	kg	Steel reinforcement for R.C.C work including straightening, cutting, bending, placing in position and binding all complete upto plinth level Thermo - Mechanically Treated bars of grade Fe-500D or more	/kg			
36	10.00	m3	Laterite neatly dressed stone of size 30 x 20 x 20 cm in CM 1:6 for super structure including cost and conveyance of all materials to site, labour charges, hire and labour charges of scaffolding, watering for curing etc, complete. as per the direction of Engineer in charge.	/cum			
37	150.00	m2	15 mm cement plaster on rough side of single or half brick wall of mix: 1:4 (1 Cement : 4 coarse sand)	/sqm			

Page8/8

Item No	Quantity	Unit	Details of work	Rate in fugures	Unit	Rate in words	Amount
38	1500.00	m2	Providing and fixing 2.50 mm thick (Black / Green colour) HDPE Nylon net fencing of required width in mesh size 40x40 mm including strengthening with 1.50 mm thick twine etc complete as per the direction of Engineer-incharge	/sqm			
			TOTAL				
						Add GST @ 18 % TOTAL	
				Rounded to	Rs.		

Rupees in words :

Signature of Name and adress

Place: Date :

Secretary